

Stainless Steel Spring Retractable Reels

Air/Water/Oil - 3/8", 1/2", 3/4", 1" I.D.

Reelcraft's stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial-solvent handling. Also suitable for coastal, offshore and on-board ship in marine applications where the harsh environment of salt water spray requires the use of stainless steel hose reels. Swivels include Viton® O-rings.

Note: Standard latch parts are made from aluminium. Stainless latch parts are available as a standard option (except 80000 Series) by placing a -S at the end. Example: OLS-S. *Series 80000 and D80000 stainless reels have an aluminum fluid path and may not be suitable for all applications.

FEATURES

- ✓ Full-flow stainless steel shaft and swivel assures maximum product delivery.
Exception: Series 80000 - aluminum fluid path.
- ✓ Heavy duty brackets eliminate bending due to angular hose pull.
- ✓ Banded drive spring gives smooth automatic hose retrieval.
- ✓ Multi-position guide arm permits wall, floor, ceiling, pit or truck mounting.
- ✓ Nylon guide rollers reduce hose drag and abrasion.
- ✓ Pos-i-latch will maintain the desired working length of hose. Mechanism assures a positive latch of the hose.
- ✓ 7000 Series offers weatherproof gasketed spring motor, assures maximum service life.
- ✓ Vibration-proof self-locking fasteners assures assembly integrity.
- ✓ 304L grade of stainless steel.



Series 7000

General Use

Many versatile applications in corrosive or sanitary environments



Series D9000

Ultra Heavy Duty

Heavy duty dual pedestal for maximum strength

Model without hose & bumper	Shipping Weight		Pressure		Hose I.D.		Hose O.D.		(F)NPTF Inlet	Hose Length		Size Index
	lbs	kg	psi	bar	in	mm	in	mm	in	ft	m	
Low and Medium Pressure Reels Maximum Temperature 210° F (99° C)												
CA 5600 OLS	22	10	500	35	3/8	10	.600	15	3/8	35	11	see pg. 9
5600 OMS	24	11	3000	207	3/8	10	.600	15	3/8	30	9	see pg. 9
AS 7800 OLS	41	19	500	35	1/2	13	.750	19	1/2	50	15	see pg. 10
7600 OMS55	42	19	3000	207	3/8	10	.710	18	3/8	66	20	see pg. 10
CA 7800 OMS	43	20	3000	207	1/2	13	.850	22	1/2	50	15	see pg. 10
82000 OLS	81	37	500	35	1/2	13	.781	20	1/2	100	30	see pg. 13
82000 OMS	83	38	1500	104	1/2	13	.820	21	1/2	75	23	see pg. 13
83000 OLS	81	37	500	35	3/4	19	1.188	30	3/4	50	15	see pg. 13
83000 OMS	83	38	1250	86	3/4	19	1.188	30	3/4	50	15	see pg. 13
D83000 OLS	84	38	500	35	3/4	19	1.188	30	3/4	75	23	see pg. 13
D84000 OLS	92	42	500	35	1	25	1.500	38	1	50	15	see pg. 13
D9200 OLS	115	52	500	35	1/2	13	.781	20	1/2	100	30	see pg. 15
D9300 OLS	116	53	500	35	3/4	19	1.188	30	3/4	75	23	see pg. 15
D9400 OLS	117	53	500	35	1	25	1.500	38	1	50	15	see pg. 15
D9200 OMS	118	54	3000	207	1/2	13	.820	21	1/2	75	23	see pg. 15
D9300 OMS	118	54	3000	207	3/4	19	1.188	30	3/4	50	15	see pg. 15

For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example D83000 OLS70.

Model without Hose & bumper	Shipping Weight		Pressure		(F)NPTF Inlet	I.D. O.D.	1/4	6	3/8	10	1/2	13	3/4	19	1	25	Size Index No. (see pg. 24)
	lbs	kg	psi	bar	in		.530	14	.688	18	.845	22	1.188	30	1.500	38	
Manual Crank Medium Pressure Reels Maximum Temperature 210° F (99° C)																	
CA HS18000 M	36	16	3000	207	1/2	Hose Length	425	130	300	91	200	61	---	---	---	---	1
HS28000 M	35	16	3000	207	1/2		625	191	450	137	300	91	---	---	---	---	2
HS19000 M	38	17	3000	207	3/4	Hose Length	425	130	300	91	200	61	75	23	---	---	1
HS29000 M	36	16	3000	207	3/4		625	191	450	137	300	91	125	38	---	---	2
HS37000 L	47	21	500	35	1	Hose Length	---	---	---	---	---	---	---	---	100	30	refer to reelcraft.com

Applications

- Restaurants
- Dairies
- Marinas
- Pharmaceutical
- Food Processing
- Ships

Available Options

Mounting Brackets
See page 47



Inlet Hose Assemblies
See page 49



Replacement Bumpers
See page 49



Replacement Hoses
See page 50

