



Motor Driven
EA33112 L12D

- ✓ Adjustable spool rotation drag that eliminates hose backlash
- ✓ Nickel-plated swivel with four "O" ring options: AFLAS (standard), Buna, Viton® or -EPR* seals
- ✓ Full flow shaft and ball bearing swivel (excludes 1/2" models)
- ✓ Permanently lubricated dual main bearings

- ✓ Motor mounting at either end of reel
- ✓ All bolted construction - no welds
- ✓ Optional lock pin to prevent spool rotation when the reel is not in use, part #S600874
- ✓ Temperature operating range from -20° F (-29° C) to +250° F (121°C)
- ✓ Vibration-proof self-locking fasteners to ensure assembly integrity *Standard swivel

Note: Many more reel models available in addition to chart

Please contact manufacturer for details

SPECIFICATIONS

MODEL	HOSE I.D.		HOSE O.D.		(F)NPTF REEL INLET	CAPACITY		WEIGHT		PRESSURE		A		B		C		D	
	in / mm	in / mm	in / mm	in / mm		ft / m	lbs / kg	psi / bar	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	
HAND CRANK																			
CA32106 L	1/2	13	.845	21	1/2	100	30	42	19	1000	69	19	483	6	152	N/A		9 3/4	248
CA32112 L	1/2	13	.845	21	1/2	200	61	49	22	1000	69	25	635	12	305	N/A		15 3/4	400
CA32118 L	1/2	13	.845	21	1/2	325	99	56	25	1000	69	31	787	18	457	N/A		21 3/4	552
CA32122 L	1/2	13	.845	21	1/2	400	122	65	29	1000	69	35	889	22	559	N/A		25 3/4	654
CA32128 L	1/2	13	.845	21	1/2	500	152	69	31	1000	69	40	1016	27	686	N/A		30 3/4	781
CA32106 M	1/2	13	.845	21	1/2	100	30	43	20	3000	207	19	483	6	152	N/A		9 3/4	248
CA32112 M	1/2	13	.845	21	1/2	200	61	49	22	3000	207	25	635	12	305	N/A		15 3/4	400
CA33106 L	3/4	19	1.188	30	3/4	50	15	43	20	1000	69	19	483	6	152	N/A		9 3/4	248
CA33112 L	3/4	19	1.188	30	3/4	100	30	49	22	1000	69	25	635	12	305	N/A		15 3/4	400
CA33118 L	3/4	19	1.188	30	3/4	175	53	56	25	1000	69	31	787	18	457	N/A		21 3/4	552
CA33112 M	3/4	19	1.188	30	3/4	100	30	49	22	3000	207	25	635	12	305	N/A		15 3/4	400
CA33118 M	3/4	19	1.188	30	3/4	175	53	56	25	3000	207	31	787	18	457	N/A		21 3/4	552
CA37118 L*	1	25	1.380	35	1	100	30	58	26	300	21	34	864	18	457	N/A		21 3/4	552
BEVEL CRANK REELS																			
BA36112 L	1/4	6	Twin Welding		1/4	250	76	57	26	200	14	25	635	12	305	N/A		15 3/4	400
BA34112 M	1/2	13	Twin Hydraulic		1/2	100	30	54	24	3000	207	25	635	12	305	N/A		15 3/4	400
ELECTRIC MOTOR DRIVEN REELS																			
EA32106 L10A	1/2	13	.845	21	1/2	100	30	63	29	1000	69	N/A	6	152	19 5/8	498	9 3/4	248	
EA32112 L12D	1/2	13	.845	21	1/2	200	61	71	32	1000	69	N/A	12	305	23 11/16	602	15 3/4	400	
EA32118 L12D	1/2	13	.845	21	1/2	325	99	77	35	1000	69	N/A	18	457	29 5/8	752	21 3/4	552	
EA33112 M12D	3/4	19	1.188	30	3/4	100	30	71	32	3000	207	N/A	12	305	23 5/8	600	15 3/4	400	
EA33128 M12D	3/4	19	1.188	30	3/4	275	84	91	41	3000	207	N/A	27	686	38 5/8	981	30 3/4	781	
EA33112 L12D	3/4	19	1.188	30	3/4	100	30	71	32	1000	69	N/A	12	305	23 5/8	600	15 3/4	400	
EA33118 L12D	3/4	19	1.188	30	3/4	175	53	71	32	1000	69	N/A	18	457	29 5/8	752	21 3/4	552	
EA33112 M24D	3/4	19	1.188	30	3/4	100	30	71	32	3000	207	N/A	12	305	23 5/8	600	15 3/4	400	
EA37118 L12D*	1	25	1.380	35	1	100	30	75	34	300	21	N/A	18	457	31	787	21 3/4	552	
AIR MOTOR DRIVEN REELS - Filter, regulator, lubricator required																			
AA32112 L4A	1/2	13	.845	21	1/2	200	61	62	28	1000	69	N/A	12	305	23 1/4	591	15 3/4	400	
AA33106 L4A	3/4	19	1.188	30	3/4	50	15	59	26	1000	69	N/A	6	152	17 1/4	438	9 3/4	248	
AA33112 L6A	3/4	19	1.188	30	3/4	100	30	62	28	1000	69	N/A	12	305	23 1/4	591	15 3/4	400	

All 30000 series reels are supplied without hose. Assemblies quoted upon request. Inlet is NPTF (F) and matches swivel size. Outlet is 1" NPTF male. *Series 37000 reels do not have a gooseneck. **Caution:** To prevent drum damage, fully extend and pressurize hose and rewind on the reel. Inlet and outlet for EA33118 L12D is 3/4"