

Operating Switches

Part No.	Specification	Use with motor
Push Button Switch		
S600870	115/230 VAC, 10 AMP fuse	S260430
600811	12/24 VDC, up to 1/3 HP	S260409, 260450
S600808	600811 switch with bracket	S260409, 260450
600869	12/24 VDC, up to 2/3 HP	S260583, S260626
260424	Momentary contact with rubber cap, 12/24 VDC	Any explosion proof motor
260425	Momentary contact, class 1 group D, for AC rewind motor. May also be used with solenoid for 12 or 24 VDC.	Any explosion proof motor



S600808



260425



600866

Part No.	Specification	Use with motor
Speed Control Switch		
600871	115/230 VAC, 10 AMP	S260430
600866	12/24 VDC	S260409, S260583, 260450, S260626

Part No.	Specification	Use with motor
Push Button Switch with Speed Control		
S600872	115/230 VAC, 10 AMP fuse, adjustable speed control	S260430
600873	115/230 VAC, 10 AMP fuse, forward/reverse adjustable speed control	
600867	DC, 25 AMP, up to 1/3 HP	S260409
600868	DC, 40 AMP circuit breaker, up to 2/3 HP	S260583



S600872

Switch Accessories

Part No.	Specification
Circuit Breaker	
S260422	40 AMP. Use with DC electric rewind motors. Manual reset button must be pressed firmly to reset.



S260422

Part No.	Specification
Starting Solenoid	
S260426	12 VDC for activation of motor.



S260426

Part No.	Specification
Mounting Bracket	
260532	Combination for circuit, solenoid and starting switch.



260532

Part No.	Specification
Junction Box	
370200	For explosion proof motor.



370200

Rewind Motors

Reels are equipped with electric or compressed air motors to drive chain and sprocket rewind mechanisms.

Part No.	Specification
Electric Motors	
S260409	Reversible type, 12 VDC 1/3 HP
260450	Reversible type, 24 VDC 1/3 HP



S260409

Part No.	Specification
Explosion Proof Electric Motors	
S260430	Reversible type, single phase, explosion proof, Class 1 Group D Division 1, 115 VAC 1/2 HP. An explosion proof, Class I Group D junction box is available for wiring A.C. motors - #370200
S260626	24 VDC 2/3 HP. Electric motor reversible type. Explosion proof.
S260583	12 VDC 2/3 HP. Electric motor reversible type. Explosion proof.



S260583

Part No.	Specification
Hydraulic Motor	
370066	1021 RPM, 668 lb-in, 2400 psi intermittent 1800 psi continuous.



370066

Part No.	Specification
Air Motors	
260428	4 AM delivers up to 1 1/2 horsepower, 1/4" N.P.T. (F) inlet.
260429	6 AM delivers up to 4 horsepower, 1/2" N.P.T.F. (F) inlet.



260429

Additional Accessories

Part No.	Specification
Chain Shrouds	
S600518	Optional chain shroud for Series 30000 and Series 1200 reels.
261746	Optional chain shroud for Series 40, 2400, 3700 and 3900 reels.



261746

Part No.	Specification
Control Valves	
260454	Pneumatic on/off flow control valve assembly, 1/4" N.P.T. (F) inlet and outlet to be used with 4 AM compressed air motors. We also recommend using a filter, regulator, and lubricator with compressed air motors.
260455	Same as above with 3/8" N.P.T.F. (F) inlet and outlet, to be used with 6 AM motors.



260454

*Reference reelcraft.com for detailed specifications.