

Product Announcement

DESCRIPTION

Reelcraft's latest edition to its H Series line holds 100' of 1" hose and features the superior corrosion resistance of 304L grade stainless steel. These reels also include a stainless brake, welded drum, and vibration proof fasteners. They are ideal for hazardous environments where corrosion is a concern.

BENEFITS

- **Superior Corrosion Resistance** - Reel is made from 304L stainless steel and offers the highest level of protection against corrosion in harsh environments.
- **Assembly Integrity** - Reel features a welded drum and vibration-proof, self-locking fasteners to insure assembly integrity.
- **Safety** - Adjustable spool rotation drag eliminates hose backlash when de-reeling.

RELATED PRODUCTS

Reelcraft manufactures a full line of industrial strength hose, cord and cable reels. For a complete product listing contact your Reelcraft representative or visit us on the web at www.reelcraft.com.

Applications

- Restaurants
- Laboratories
- Chemical Plants
- Car Washes
- Marinas
- Food Processing



HS37000 L


Model (without hose)	Drive Type	Hose I.D.		Hose O.D.		CAPACITY		Pressure		Weight		Size Index
		in / mm	in / mm	ft / m	psi / bar	lbs / kg						
HS37000 L	Hand Crank	1 25.4	1.380 35	100 31	500 35	47 21	1					
EHS37000 L12DX	12v DC Exp. Proof	1 25.4	1.380 35	100 31	500 35	72 32	2					
EHS37000 L10A	115 v AC	1 25.4	1.380 35	100 31	500 35	72 32	2					

NOTE: Motor and sprocket are not stainless steel.



Reelcraft Industries is
ISO 9001:2008
Certified Since 1996

No.	Size Index	
	1	2
DIM.	in / mm	in / mm
A	22 1/2 572	22 1/2 572
B	21 534	21 534
C	10 254	10 254
D	18 1/4 464	18 1/4 464
E	20 7/8 530	20 7/8 530
F	31 1/2 800	29 737
4 - 7/16" mounting holes		



SPECIFICATIONS

- ✓ Maximum temperature rating 210°F (99° C)
- ✓ 304L grade stainless steel
- ✓ Full-flow stainless steel shaft and balanced swivel
- ✓ Adjustable spool rotation drag
- ✓ All bolted frame construction
- ✓ Electro polish finish
- ✓ 316 stainless steel fluid path

Part #	Pressure	Description
Accessory Hose Assemblies		
600982-100	300 21	1"NPT(M) x 1"NH(F) x 100'
600982-150	300 21	1"NPT(M) x 1"NH(F) x 150'
600982-200	300 21	1"NPT(M) x 1"NH(F) x 200'
Low pressure PVC braided hose.		



Part #	Pressure	Description
Accessory Inlet Hose Assemblies		
600982-10	300 21	1"NPT(M) x 1"NH(F) x 10'
Low pressure PVC braided hose.		



Reelcraft Industries, Inc.
2842 E. Business Hwy. 30
Columbia City, IN 46725
Fax: **260-248-2605**

Toll Free Ph: **800-444-3134**
Ph: **260-248-8188**
www.reelcraft.com
reelcraft@reelcraft.com

