

New Product Announcement

Light Duty Hand Crank Hose Reels

CU Series Air/Water - 3/8" & 1/2" I.D.

Reelcraft's Series CU are designed for lighter-duty applications that require longer lengths of low pressure air/water hose. Hand crank with a balanced brass swivel and brass inlet, Series CU is the product of lighter weight components and forward-thinking design. The series CU is an economical choice for storing and retrieving hose.

CT Series Pressure Wash - 3/8" I.D.

Reelcraft's Series CT conveniently stores longer lengths of high pressure wash hose. These reels feature a balanced brass swivel and brake assembly attached to the main shaft, eliminating de-spooling when reel is not in use. The inlet hose connects to the swivel through the tubular base. The reel is powder coated at the component level for maximum corrosion resistance.



NEW!
CT6050HN

✓ Superior corrosion-resistance

Components are powder coated prior to assembly for maximum corrosion resistance

✓ Reel protects hose

Reel stores long lengths of expensive hose out of harm's way. Hose makes smooth transition onto reel to minimize friction.

✓ Innovative braking mechanism

CU & CT Series feature a unique friction brake that prevents de-spooling of hose while reel is not in use.

CU SERIES			
No.	A	B	C
Dim.	in / mm	in / mm	in / mm
CU6050LN	11 1/2 292	16 3/4 416	11 279
CU6100LN	11 1/2 292	20 4/5 365	11 279
CU8050LN	14 3/10 364	16 3/4 425	13 1/4 337
CU8100LN	14 3/10 364	20 4/5 529	13 1/4 337

Four 3/8" slotted mounting holes

CT SERIES			
No.	A	B	C
Dim.	in / mm	in / mm	in / mm
CT6050HN	15 2/3 397	15 2/5 416	13 1/4 337
CT6100HN	15 2/3 397	19 4/9 365	13 1/4 337

Four 3/8" mounting holes



CU6050LN

Model without Hose	Weight		Pressure		Hose I.D.		Hose O.D.		(M)NPTF Outlet	(F)NPTF Inlet	Hose Length	
	lbs	kg	psi	bar	in	mm	in	mm	in	in	ft	m
Low Pressure Air/Water Reels Maximum Temperature 150° F (65° C)												
CU6050LN	10	4.5	300	21	3/8	10	.600	15	3/8	3/8	50	15
CU6100LN	13	6	300	21	3/8	10	.600	15	3/8	3/8	100	30
CU8050LN	12	5.8	300	21	1/2	13	.750	19	1/2	1/2	50	15
CU8100LN	17	8	300	21	1/2	13	.750	19	1/2	1/2	100	30
High Pressure Wash Reels Maximum Temperature 210° F (99° C)												
CT6050HN	10	4.5	5000	345	3/8	10	.600	15	3/8	1/2	50	15
CT6100HN	13	6	5000	345	3/8	10	.600	15	3/8	1/2	100	30

NOTE: To prevent drum damage due to crushing, all hoses must be fully de-spooled before pressurization.

Reelcraft Industries, Inc.
2842 E. Business Hwy. 30
Columbia City, IN 46725
Fax: 260-248-2605

Toll Free Ph: 800-444-3134
Ph: 260-248-8188
www.reelcraft.com
reelcraft@reelcraft.com

