

GFCI Protected Duplex Box

Series L 4000 & L 5000

Product Improvement Announcement

DESCRIPTION

Reelcraft now features the Hubbell non-metallic portable outlet Box. It incorporates a PowerPort® portable outlet box with ground fault protected duplex receptacle that contains a Circuit Guard® GFCI module and receptacle. The Circuit Guard® GFCI module is rated for up to 20 AMPs and the receptacles can be ordered as either 15 or 20 AMPs. The Circuit Guard® GFCI module contains an open neutral protection feature that allows the GFCI module to trip if a neutral wire is broken, thus reducing the risk of electrical shock. Once the GFCI has been tripped, it will not reset until the circuit is completed. The updated design satisfies all UL requirements for GFCI's standard, UL 943, section 6.7.2.1c, which requires open neutral protection for a portable GFCI.

BENEFITS

- **Safety** Duplex box is designed for high visibility and when installed properly, will reduce risk associated with electrical shock.
- **Durability** Heavy duty composite case is designed to be shock and wear resistant.

RELATED PRODUCTS

Reelcraft offers a complete line of over 2,500 hose, cord and cable reels. For more information visit us on the web at www.reelcraft.com.



Panel on reverse side with GFCI LED and reset/test button.



Model Shown: L 4545 123 7



SPECIFICATIONS

MODEL AFFECTED	ACCESSORY	CORD SPECIFICATIONS				VOLTS *	AMPS	WEIGHT	
		AWG / mm ²	No. Cond.	Length ft / m	Type			lbs	kg
L 4545 123 7A	Duplex Outlet Box w/ GFCI	12 3.32	3	45 14	SJEOW	125	20	28	13
L 4545 123 7	Duplex Outlet Box w/ GFCI	12 3.32	3	45 14	SJEOW	115	15	29	14
L 5550 123 7	Duplex Outlet Box w/ GFCI	12 3.32	3	50 15	STOW	115	15	47	21

*All models UL listed at 115 Volts 60 Hz single phase. Base power cord reels without plug are suitable for 220 Volt. **Inlet plug is NEMA-15P configuration. for use in dry, indoor, non-hazardous locations only.

NOTE: PowerPort® and Circuit Guard® are registered trademarks of Hubbell Corporation.

SPECIFICATIONS

- ✓ Meets UL standard UL 943, section 6.7.2.1c requiring open neutral protection for a portable GFCI.
- ✓ Flip top box lid with compression foam creates a seal between electrical components and lid.
- ✓ High visibility yellow
- ✓ Stainless steel hardware
- ✓ Two outlets rated at 15 or 20 AMPS
- ✓ Led indicator light lets user know when box is receiving power
- ✓ Reset/test buttons on reverse side of box

North America: 800-444-3134
 Europe: +44 (0) 1536 406999
 Pacific Rim: +63-45-599-3721
 China: (519) 8512 2391
 Latin America: 002-60-489-1685

Reelcraft Industries, Inc.
 One Reelcraft Center / P.O. Box 248
 Columbia City, IN 46725
 FAX: 260-248-2605
www.reelcraft.com

Reelcraft Industries is
ISO 9001:2000
 Certified Since 1996

 **REELCRAFT**
 Wind Things Up With Reelcraft™

GFCI PROTECTED DUPLEX BOX / SERIES L 4000 & L 5000