

# New Product Announcement | Series PAV

## Pavement Breaker Reels Series PAV

Keep hose out of harm's way while on the job site with the new PAV series from Reelcraft. These industrious reels are designed to supply pavement breakers with up to 75' of 3/4" rubber air hose. The special braided hose is abrasion resistant and features a 3/4" universal air coupling for quick and easy disconnects. These reels feature a high level of corrosion resistance due to an individual component powder coating process that takes place prior to assembly.

### Benefits

- **Structural Strength** - Heavy gauge steel stampings with re-enforced ribs give added strength.
- **Dependable** - The latch mechanism is mounted on the base to eliminate latch-out at full extension and ensure the hose retracts every time.
- **Built for Pavement Breakers** - Reels are outfitted with premium grade rubber hose and crimped universal coupler w/ safety clip, Ideal for running large air tools.
- **Versatile Mounting** - Guide arm can be adjusted to several different locations.
- **Corrosion Resistance** - Steel components are powder coated for maximum resistance to the elements.

### Related Products

Reelcraft offers a complete line of over 2,500 hose, cord and cable reels. Other reels suitable for pavement breaking include our 9000 Series which holds up to 100' of 3/4" and our 30000 Series hand crank reel for even longer lengths of 3/4" hose. For more information visit us online at [www.reelcraft.com](http://www.reelcraft.com) or call toll free 800-444-3134.

	Dimensions - Size Index					
	1		2		3	
	in	mm	in	mm	in	mm
<b>A</b>	20 <sup>1</sup> / <sub>4</sub>	514	25 <sup>3</sup> / <sub>8</sub>	645	25 <sup>3</sup> / <sub>8</sub>	645
<b>B</b>	19 <sup>3</sup> / <sub>4</sub>	502	24	610	24	610
<b>C</b>	7 <sup>13</sup> / <sub>16</sub>	198	10	254	10 <sup>1</sup> / <sub>2</sub>	267
<b>D</b>	3 <sup>7</sup> / <sub>8</sub>	98	6	152	7 <sup>7</sup> / <sub>8</sub>	200
<b>E</b>	7	178	10 <sup>1</sup> / <sub>2</sub>	267	13	330
<b>F</b>	N/A		8 <sup>1</sup> / <sub>8</sub>	206	10 <sup>3</sup> / <sub>8</sub>	264



PAVD83075 OLP

### SPECIFICATIONS

- Heavy gauge steel construction
- Fully enclosed drive spring
- Buna N seals
- Max temperature rating 180 °F (82 °C)
- Universal air coupling (Chicago style) and safety clip
- For pressures up to 250 PSI
- High quality rubber hose
- Individual powder coated components

Made  
  
in USA

Model with hose	Shipping Weight		Hose I.D.		Hose Length		Pressure		Size Index
	lbs	kg	in	mm	ft	m	psi	bar	
PAV7925 OLP	54	25	3/4	19	25	8	250	18	1
PAV83050 OLP	90	41	3/4	19	50	15	250	18	2
PAVD83075 OLP	140	59	3/4	19	75	23	250	18	3

Hose is rated for low pressure air. Consult manufacturer for other applications.