

# New Product Announcement

## Twin Pack Reels Air/Water & Electric

Reelcraft now offers its most popular hose and cord reel models as a convenient package. Reelcraft twin packs are ideal for customers looking to outfit a bench/ work station with both power/lighting and pneumatics. It is now even easier to order with only one part number, one price and combine on shipping. Other model combinations are available upon request.

### Benefits

- **Improved Efficiency** air and power where and when you need it.
- **Increased Safety** reduce injury incidence due to slips, trips & falls
- **Improved Productivity** less time spent managing unwieldy coiled hose/cord.
- **Reduce Hose Wear** store hoses/cords out of harms way.

### Related Products

Reelcraft is home to an extensive line of more than 2500 hose, cord, and cable reels. For an expanded list of our product offering visit us on the web at [www.reelcraft.com](http://www.reelcraft.com) or contact a customer service representative at 1-800-444-3134.



Model Shown:  
TP5650 OLP/L 4545 123 3

Model	Hose Reel Specifications					Cord Reel Specifications							
	Hose I.D. in / mm	Hose Length ft / m	Pressure psi / bar	AWG / mm	No. Cond.	Volts	Amps	Type	Length ft / m	Accessory			
<b>Economic Air/Water &amp; Electric Reels</b> Max Temperature 150°F (65°C)													
TPRT635-OLP/LD2030 143 9	3/8 10	35 11	300 21	14 2.08	3	125	13	SJTW	30 9	Grounded Triple Outlet			
TPRT650-OLP/LG3050 143 9	3/8 10	50 15	300 21	14 2.08	3	125	13	SJTW	50 15	Grounded Triple Outlet			
TPRT635-OLP/LG3050 163 8	3/8 10	35 11	300 21	16 1.33	3	120	10	SJTW	50 15	13 watt FL Light w/ Outlet			
TPRT650-OLP/LG3050 163 8	3/8 10	50 15	300 21	16 1.33	3	120	10	SJTW	50 15	13 watt FL Light w/ Outlet			
TPRT650-OLP/LD2040 163 2	3/8 10	50 15	300 21	16 1.33	2	120	.3	SJTW	40 9	13 watt FL Light			
TPRT650-OLP/L 4545 123 3	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Single Receptacle			
TPRT650-OLP/L 4545 123 7	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Duplex Outlet Box w/ GFCI			
TP4625 OLP/LD2030 143 9	3/8 10	25 8	300 21	14 2.08	3	125	13	SJTW	30 9	Grounded Triple Outlet			
TP4625 OLP/LD2030 163 2	3/8 10	25 8	300 21	16 1.33	3	120	.3	SJTW	30 9	13 watt FL Light			
<b>Premium Air/Water &amp; Electric Reels</b> Max Temperature 150°F (65°C)													
TP5635 OLP/LG3040 123 9	3/8 10	35 11	300 21	12 3.32	3	125	15	SJTW	40 9	Grounded Triple Outlet			
TP5635 OLP/L 4545 123 3	3/8 10	35 11	300 21	12 3.32	3	125	15	SJEOW	45 14	Single Receptacle			
TP5650 OLP/L 4050 163 3	3/8 10	50 15	300 21	16 1.33	3	125	13	SJTOW	50 15	Single Receptacle			
TP5650 OLP/L 4545 123 3	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Single Receptacle			
TP5650 OLP/L 4545 123 7	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Duplex Outlet Box w/ GFCI			
TP5650 OLP/L 4050 163 1	3/8 10	50 15	300 21	16 1.33	3	125	13	SJTOW	50 15	IN Light w/ Outlet			
TP5635 OLP/L 4035 163 8	3/8 10	35 11	300 21	12 3.32	3	125	10	SJTO	35 11	13 watt FL Light w/ Outlet			
TP5650 OLP/L 4050 163 8	3/8 10	50 15	300 21	12 3.32	3	125	10	SJTO	50 15	13 watt FL Light w/ Outlet			
TP5650 OLP/L 4050 162 2	3/8 10	50 15	300 21	12 3.32	2	125	.3	SJTOW	50 15	13 watt FL Light			
<b>Heavy Duty Industrial Air/Water &amp; Electric Reels</b> Max Temperature 150°F (65°C)													
TP7650 OLP/L 4545 123 3	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Single Receptacle			
TP7650 OLP/L 4545 123 7	3/8 10	50 15	300 21	12 3.32	3	125	15	SJEOW	45 14	Duplex Outlet Box w/ GFCI			
TP7650 OLP/L 4050 163 8	3/8 10	50 15	300 21	16 1.33	3	125	10	SJTO	50 15	13 watt FL Light w/ Outlet			
TP7670 OLP/L 4545 123 3A	3/8 10	70 22	300 21	12 3.32	3	125	20	SJEOW	45 14	20 AMP Single Receptacle			
TP7670 OLP/L 5550 123 7	3/8 10	70 22	300 21	12 3.32	3	125	15	SJEOW	50 15	Duplex Outlet Box w/ GFCI			
TP7850 OLP/L 4545 123 3A	1/2 13	50 15	300 21	12 3.32	3	125	20	SJEOW	45 14	20 AMP Single Receptacle			
TP7850 OLP/L 4545 123 7A	1/2 13	50 15	300 21	12 3.32	3	125	20	SJEOW	45 14	Duplex Outlet Box w/ GFCI			
TP7850 OLP/L 5550 123 7	1/2 13	50 15	300 21	12 3.32	3	125	15	SJEOW	50 15	Duplex Outlet Box w/ GFCI			

NOTE: Electric reels rated for indoor non-weather tight applications. Consult our main catalog or a member of customer service for additional reel specifications.

**Reelcraft Industries, Inc.**  
2842 E. Business Hwy. 30  
Columbia City, IN 46725  
Fax: **260-248-2605**

Toll Free Ph: **800-444-3134**  
Ph: **260-248-8188**  
[www.reelcraft.com](http://www.reelcraft.com)  
[reelcraft@reelcraft.com](mailto:reelcraft@reelcraft.com)

