



**SERIES 4000**

# Premium Duty Spring Retractable Reels



4625 OLP

Compact for a wide range of applications with critical space requirements

Guide arm adjusts to two positions

Inlet hose is plumbed into the base to eliminate the risk of undue stress on the swivel

Bent tube swivel design offers a smooth hose transition onto the spool; Swivel is nested inside the spool for protection from impact and the environment

Feliable speed latch allows for positive locking of the spool in two positions per rotation

All steel components are powder coated for maximum corrosion resistance



AIR



WATER

**I.D. Hose Sizes**

**1/4", 3/8"**

## Reel Accessories

Part	Part Number	Specifications
Pivot Base	S600608	340°, Color: Black
Swing Bracket	600626	Wall Mount, Color: Black
Swing Bracket	600993	Wall Mount, Color: Red
Inlet Hose	Visit <a href="http://reelcraft.com">reelcraft.com</a> for more information	



1.800.444.3134 | [reelcraft.com](http://reelcraft.com)


Model with Hose and Bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in
<b>Low Pressure Air/Water Reels</b>													
Maximum Temperature 150°F (65°C) Maximum Working Pressure is at 70°F (20°C)													
4420 OLP	18	8	1/4	6	.475	12	20	6	300	21	1/4	3/8	1/4
4425 OLP	19	9	1/4	6	.475	12	25	8	300	21	1/4	3/8	1/4
4435 OLP	19	9	1/4	6	.475	12	35	11	300	21	1/4	3/8	1/4
<b>4625 OLP*</b>	20	9	3/8	10	.600	15	25	8	300	21	1/4	3/8	1/4

\*Most popular models | Low pressure reels supplied with PVC hose. See operating instructions for optimum mounting configuration.

Model without Hose and Bumper	Shipping Weight		Hose Capacity						Max Pressure		NPT(F) Reel Inlet	NPT(F) Reel Outlet	
	lbs	kg	Hose I.D.		Hose O.D.		Hose Length		psi	bar	in	in	
<b>Low Pressure Air/Water Reels</b>													
Maximum Temperature 210°F (99°C)													
4400 OLP	17	8	1/4	6	.475	12	35	11	500	35	3/8	1/4	
4600 OLP	17	8	3/8	10	.600	15	25	8	500	35	3/8	1/4	

Dimensions - Size Index

	in	mm
A	12 7/8	327
B	12 5/8	321
C	8	203
D	2 1/2	64
E	5 5/8	143



Additional Models Available for:



CORD



Interactive Reel Catalog

