

## Spring Retractable, Hand Crank, Motor Driven Hose Reels

**Water** - 1/4", 3/8", 1/2" I.D.

- Compact design and quality steel construction
- The high pressure water swivel is designed to handle a broad range of pressures, temperatures, and chemicals
- Ideal for agricultural, marine, equipment cleaning, and pressure washing applications
- Individually powder coated components offer maximum protection from premature corrosion
- Models without hose are rated up to 5000 PSI
- Full flow swivel combines the highest grade seal design and materials with bearing areas to ensure maximum service life
- Available in hand crank, spring driven, or electric motor driven models



CT6100HN



CA38106 M



PW7650 OHP

Models with a ★ icon are our most popular models.

	in	mm	in	mm	in	mm	Shipping Weight	Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #		
Hose I.D.	1/4	6	3/8	10	1/2	13								
Hose O.D.	.530	13	.730	19	.850	22								
Model without hose	Hose Length													
	ft	m	ft	m	ft	m	lbs	kg	psi	bar	in	in		
Manual Hand Crank Pressure Wash Reels    Maximum Temperature 210 °F (99 °C)														
CT6050HN	---	---	50	15	---	---	13	6	5000	345	1/2	3/8	---	1
CT6100HN	---	---	100	30	---	---	17	8	5000	345	1/2	3/8	---	2
CA38106 M	200	61	140	43	100	30	41	19	5000	345	1/2	1/2	25	---
CA38112 M	425	130	300	91	200	61	46	21	5000	345	1/2	1/2	25	---
Electric Motor Driven Pressure Wash Reels    Maximum Temperature 212 °F (100 °C)														
EA38106 M12D	200	61	140	43	100	30	63	29	5000	345	1/2	1/2	25	---
EA38112 M12D	425	130	300	91	200	61	71	32	5000	345	1/2	1/2	25	---

PSI rating based upon 2.4 to 1 safety factor.

Model with hose & bumper	Shipping Weight	Hose I.D.	Hose O.D.	Hose Length	Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #
	lbs kg	in mm	in mm	ft m	psi bar	in	in	in		
<b>Spring Retractable Pressure Wash Reels</b> Maximum Temperature 210 °F (99 °C)										
PW7650 OHP ★	60 27	3/8 10	.730 19	50 15	4800 331	1/4	1/2	3/8	12	---
PWD76075 OHP	90 41	3/8 10	.730 19	75 23	4800 331	1/4	1/2	3/8	13	2
PW81100 OHP	119 54	3/8 10	.730 19	100 30	4800 331	3/8	1/2	3/8	14	1

PSI rating based upon 2.4 to 1 safety factor.

Model without hose & bumper	Shipping Weight	Hose Capacity			Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #
	lbs kg	I.D.	O.D.	Length	psi bar	in	in		
		in mm	in mm	ft m					
<b>Spring Retractable Pressure Wash Reels</b> Maximum Temperature 210 °F (99 °C)									
PW7600 OHP	43 20	3/8 10	.730 19	50 15	5000 345	1/2	3/8	12	---
PW81000 OHP ★	86 39	3/8 10	.730 19	100 30	5000 345	1/2	3/8	14	1

PSI rating based upon 2.4 to 1 safety factor.

Dimensions				
	1		2	
	in	mm	in	mm
A	15 <sup>5</sup> / <sub>8</sub>	397	15 <sup>5</sup> / <sub>8</sub>	397
B	13 <sup>1</sup> / <sub>4</sub>	337	13 <sup>1</sup> / <sub>4</sub>	337
C	3 <sup>1</sup> / <sub>2</sub>	89	3 <sup>1</sup> / <sub>2</sub>	89
D	4 <sup>1</sup> / <sub>4</sub>	108	4 <sup>1</sup> / <sub>4</sub>	108
E	15 <sup>1</sup> / <sub>2</sub>	394	19 <sup>1</sup> / <sub>2</sub>	495
F	6	152	6	152



**Interactive Reel Catalog**

Visit [reelcraft.com/catalog](http://reelcraft.com/catalog) for complete product specifications, parts, and accessories.



**High Pressure Hose Assemblies & Bumper Stops**  
See pages 36-37